

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/048845 A1

(51) International Patent Classification⁷: **A61B 6/06**

(74) Agent: CHINA PATENT AGENT (H.K.) LTD.; 22/F,
Great Eagle Centre, 23 Harbour Road, Wanchai, Hong
Kong (HK).

(21) International Application Number:
PCT/CN2003/000985

(22) International Filing Date:
20 November 2003 (20.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): GE
MEDICAL SYSTEMS GLOBAL TECHNOLOGY
COMPANY, LLC. [US/US]; 3000 North GrandView
Boulevard-W-710, Waukesha, WI 53188 (US).

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): YANG, Zhao
[CN/CN]; N0. 2 North Yong Chang Road, Beijing
Economic & Technological Development Area, Beijing
100176 (CN).

Published:

— with international search report

[Continued on next page]

(54) Title: COLLIMATOR AND RADIATION IRRADIATOR



(57) Abstract: A collimator capable of being reduced in its external size without sacrificing an aperture is to be provided. To this end, the collimator comprises a pair of first plate members which defines a radiation passing aperture by a spacing between respective opposed end faces, a pair of second plate members which respectively overlap the first plate members at least partially so as to block any other radiation than the radiation passing through the aperture, a pair of third plate members which respectively overlap the second plate members at least partially so as to block any other radiation than the radiation passing through the aperture, an adjusting mechanism which adjusts the aperture by moving the pair of first plate members, and a follow-up mechanism which causes the pair of second plate members to move following the pair of first plate members with movement of the first plate members.

WO 2005/048845 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.